

# System-configurator vicosys® 5400

## Basic Device

- |                                     |          |  |
|-------------------------------------|----------|--|
| <input checked="" type="checkbox"/> | 4-21-165 | <b>vicosys® 5400 Industrial-PC Basic Device</b><br>embedded industrial-PC based on x86 <ul style="list-style-type: none"> <li>• Intel(R) Core(TM) i3-6102E CPU @ 1.90GHz, 2 GB DDR3L RAM</li> <li>• 4 GB CF-card memory</li> <li>• 1 x CAN bus interface</li> <li>• 1 x RS232 interface</li> <li>• 4 x Input / 4 x Output – digital interface (24V)</li> </ul> |
|-------------------------------------|----------|--|

## Software Licenses

- |                                     |          |  |
|-------------------------------------|----------|--|
| <input checked="" type="checkbox"/> | /        | software license vicosys® basic                |
| <input type="checkbox"/>            | 4-20-209 | software license vicosys® thermography         |
| <input type="checkbox"/>            | 4-20-210 | software license vicosys® asynchronous process |

## Camera Interface Cards

Choose **one** card

- |                                     |          |  |
|-------------------------------------|----------|--|
| <input checked="" type="checkbox"/> | 4-21-176 | <b>Camera interface GigE 4 x 1000 Mbit</b> <ul style="list-style-type: none"> <li>• includes vicosys® GigE-Vision license</li> </ul> |
|-------------------------------------|----------|--|

## I/O-Cards

Choose **one optional** card

- |                          |          |  |
|--------------------------|----------|--|
| <input type="checkbox"/> | 4-21-170 | <b>Digital I/O Card ADDI DATA</b> <ul style="list-style-type: none"> <li>• 16 digital inputs, 24 V or 12 V</li> <li>• 16 digital outputs, 10 V ... 36 V, 500 mA per channel</li> <li>• output type <b>Open Emitter</b> (PNP)</li> <li>• isolated inputs and outputs, 1000 V<sub>RMS</sub></li> </ul>             |
| <input type="checkbox"/> | 4-21-171 | <b>Digital I/O Card ADLINK</b> <ul style="list-style-type: none"> <li>• 16 digital inputs, 0 V... 24 V (non polarity)</li> <li>• 16 digital outputs, 5 V ... 35 V, 500 mA per channel</li> <li>• Output type <b>Open Collector</b> (NPN)</li> <li>• isolated inputs and outputs, 2500 V<sub>RMS</sub></li> </ul> |
| <input type="checkbox"/> | 4-21-174 | <b>Sercos III Card AUTOMATA</b> <ul style="list-style-type: none"> <li>• Automata Sercos III PCIe card, 1 slave</li> </ul>   |
| <input type="checkbox"/> | 4-21-175 | <b>PROFINET Card HILSCHER</b> <ul style="list-style-type: none"> <li>• Hilscher CIFX 50E-RE PCI Express PROFINET</li> </ul>  |

## Mounting Accessories

- |                          |          |  |
|--------------------------|----------|--|
| <input type="checkbox"/> | 4-21-167 | <b>Mounting set 5300/5400</b> <ul style="list-style-type: none"> <li>• mounting adapter, for an easy replacement of vicosys® 4300</li> </ul> |
|--------------------------|----------|--|