
vicolux® Telecentric Light - TZB130-G525/UDC/-a

Short description: telecentric light, green, If diameter: 130 mm, flashable by flash controller

Order number: 1-10-959

EAN: 4251692646595



Characteristics

- flashable telecentric LED lighting - parallel (collimated) beam path
 - ideal as backlight in combination with telecentric lenses
 - for the targeted highlighting of edges and surface structures as well as for the detection of inclusions and defects in transparent materials
 - connection: cable with M8 connector
 - diverse attachment options and extensive accessories
-


Technical data

Light-emitting surface	Diameter: 130 mm
Light design	Telecentric
Light colour (typ.)	Grün, 525 nm
Special feature	Flashable max. 0,5 ms und 15% on-time
Continuous current (I_{LED})	max. 30 mA
Pulse mode	$2 \times I_{LED}$
Flash mode	$5 \times I_{LED}$
Housing material	Aluminium, black anodised
Optical material	Glass
Filter thread	M144 x 0.75 - depth 5 mm
Weight	5.000 g
Degree of protection	IP50
Safety class	Class III, safety extra low voltage (SELV)
Risk group (DIN EN 62471)	Risk group 0 (exempt group)
Ambient temperature	0 °C ... 45 °C


Notices

The lighting can only be operated in conjunction with a suitable Current source.

Drawings



Dimensional drawing in mm



Pin assignment: M8 connector