Vision & Control GmbH
Phone: +49 36 81 / 79 74 11
www.vision-control.com

vicolux® Spot Light - RAL10-7-R625/C

Short description: compact spot light, red, beam angle 7 degree, controlled

Order number: 1-11-500

EAN: 4251692648049

Characteristics

- LED spot light with direct illumination
- homogeneous illumination
- lighting controller integrated in casing
- continuous or pulsed operation
- pulse-length and brightness adjustable
- connection: M5 plug on the casing

Vision & Control GmbH
Phone: +49 36 81 / 79 74 11
www.vision-control.com

Technical data

Light colour	Rot, 625 nm
Beam angle	7°
Operation voltage	24 VDC (10 - 30 V)
Housing material	Aluminium, black anodised
Weight	22 g
Degree of protection	IP65
Safety class	Class III, safety extra low voltage (SELV)
Risk group (DIN EN 62471)	Risk group 0 (exempt group)
Ambient temperature	0 °C ... 40 °C

Vision & Control GmbH
Phone: +49 36 81 / 79 74 11
www.vision-control.com

Accessories for Spot lights - RAL10-7-R625/C

Order number	Title	Description
Accessories for RAL10 series		
1-11-751	Diffuser 15% RAL10	for RAL10, diffuser plate made of PMMA, incl. screws
1-11-752	Diffuser 40% RAL10	for RAL10, diffuser plate made of PMMA, incl. screws
1-11-750	Polarizer linear RAL10	for RAL10, neutral gray polarization filter, incl. screws
Connection cable M5-4pin		
1-11-117	Cable-M5-4p-1A-straight-2m	4x0.14mm², 1A, 60V, PUR, IP67, M5-4pin straight socket to free cable end
1-11-116	Cable-M5-4p-1A-straight-5m	4x0.14mm², 1A, 60V, PUR, IP67, M5-4pin straight socket to free cable end
1-11-105	Cable-M5-4p-1A-angled-2m	4x0.14mm², 1A, 60V, PUR, IP67, M5-4pin angled socket to free cable end
1-11-104	Cable-M5-4p-1A-angled-5m	4x0.14mm², 1A, 60V, PUR, IP67, M5-4pin angled socket to free cable end

Vision & Control GmbH
Phone: +49 36 81 / 79 74 11
www.vision-control.com

Drawings



Dimensional drawing in mm



Pin	Core colour	Signal	Description
1	BN (brown)	V+	Operating voltage
2	WH (white)	CV	Control voltage
3	BU (blue)	GND	Ground
4	BK (black)	ON/OFF	Switch input

Pin assignment: M5 connector