

vicolux® Bar Light - LDL7x250-W5K7/24V/EX- Luminous Field Size 7 mm x 250 mm

Short description: bar light, white, diffuse, lf-size: 7 mm x 250 mm, static/switchable, external

Order number: 1-16-566

EAN: 4251692672778

Actual Notice: **Not for new developments** Please use the revised variant "-a" for new developments.



Characteristics

- LED bar light with diffuse illumination
 - homogeneous illumination
 - lighting controller external
 - continuous or pulsed operation
 - brightness pre-set, flash duration corresponds to pulse-length
 - connection: M5 plug at lighting controller
 - metal casing, optical material: PMMA
 - multiple mounting options
-

Technical data

Luminous field	7 mm x 250 mm
Light colour	Weiss, 5700 K
Light design	Diffuse
Radiance	51 W/(m ² *sr)
Luminance	17000 cd/m ²
Operation voltage	24 VDC (12 - 30 V)
Ambient temperature	-10°C bis +45°C
Degree of protection	IP50
Housing material	Aluminium black anodised
Weight	60 g
Risk group (DIN EN 62471)	Risk group 0 (exempt group)
Safety class	III, Schutzkleinspannung (SELV)


Notices

For further information, please contact your personal contact in our sales department.


Accessories for Area and Bar lights - LDL7x250-W5K7/24V/EX

Order number	Title	Description
<i>Mounting Systems</i>		
1-16-826	Tension clamp LxL7 series	for variable attachment and extension of the LxL7 series, l=25mm, w=17mm
<i>Connection cable M5-4pin</i>		
1-11-117	Cable-M5-4p-1A-straight-2m	4x0.14mm ² , 1A, 60V, PUR, IP67, M5-4pin straight socket to free cable end
1-11-116	Cable-M5-4p-1A-straight-5m	4x0.14mm ² , 1A, 60V, PUR, IP67, M5-4pin straight socket to free cable end
1-11-105	Cable-M5-4p-1A-angled-2m	4x0.14mm ² , 1A, 60V, PUR, IP67, M5-4pin angled socket to free cable end
1-11-104	Cable-M5-4p-1A-angled-5m	4x0.14mm ² , 1A, 60V, PUR, IP67, M5-4pin angled socket to free cable end


Drawings




light unit



controller unit



Dimensional drawing in mm: length = 250 mm; width = 7 mm

Function	Symbol	Cable Colour*	Pin	Contact arrangement
Operating Voltage	V+	brown	1	
Ground	GND	blue	3	
Switch Input	ON/OFF	black	4	
Not connected	NC	white	2	

* for recommended accessories

Pin assignments, M5 connector