
vicolux® Area Light - DL30x30-R633/24V

Short description: area light, red, diffuse, lf-size: 30x30 mm,
M5-4pin, static / switchable

Order number: 1-18-300

EAN: 4251692658048



Characteristics

- LED area light with diffuse illumination
 - homogeneous illumination
 - lighting controller integrated in casing
 - continuous or pulsed operation
 - brightness pre-set, flash duration corresponds to pulse-length
 - connection: M5 plug on the casing
 - metal casing, optical material: PMMA
-


Technical data

Light-emitting surface	30 mm x 30 mm
Light colour	Red, 633 nm
Light design	Diffuse
Operating voltage	24 V
Power consumption	1.5 W
Radiance	
• Continuous operation	100 W/(m ² sr)
Housing material	Aluminium, black anodised
Optical material	PMMA
Weight	35 g
Degree of protection	IP50
Safety class	Class III, safety extra low voltage (SELV)
Risk group (DIN EN 62471)	Exempt
Ambient temperature	0 °C to 45 °C


Accessories for Area and Bar lights - DL30x30-R633/24V

Order number	Title	Description
Beam splitter STE30x30		
1-18-031	Adapter STE30x30 - DL30x30	Attachment of the STE30x30 to the DL30x30
Mounting systems		
1-18-070	Adjustable holder xL30	for xL30x30/60/90, stepless rotatable and swiveling mounting, incl. screws
diffusers		
1-18-060	Diffusor 40% 30x30x1	for AL30x30 diffuser plate made of PMMA, screwable
Polarisers for Area Lights		
1-18-062	Polarizer linear 30x30x0.18	for AL30x30 and DL30x30, polarizing filter, neutral gray, self-adhesive
protective covers		
1-18-061	Clear cover 30x30x1	for AL30x30, protective cover made of PMMA, screwable
Connection cable M5-4pin		
1-11-117	Cable-M5-4p-1A-straight-2m	4x0.14mm ² , 1A, 60V, PUR, IP67, M5-4pin straight socket to free cable end
1-11-116	Cable-M5-4p-1A-straight-5m	4x0.14mm ² , 1A, 60V, PUR, IP67, M5-4pin straight socket to free cable end
1-11-105	Cable-M5-4p-1A-angled-2m	4x0.14mm ² , 1A, 60V, PUR, IP67, M5-4pin angled socket to free cable end
1-11-104	Cable-M5-4p-1A-angled-5m	4x0.14mm ² , 1A, 60V, PUR, IP67, M5-4pin angled socket to free cable end

Drawings



Dimensional drawing in mm



Pin assignment of the M5 connector