

---

## vicolux® Bar Light - LDL7x75-R625/24V/EX/-a- Luminous Field Size 7 mm x 75 mm

---

**Short description:** bar light, red, diffuse, lf-size: 7 mm x 75 mm, static/switchable, external

**Order number:** 1-34-540

**EAN:** 4251692676387



---

### Characteristics

- LED bar light with diffuse illumination
  - homogeneous illumination
  - lighting controller external
  - continuous or pulsed operation
  - brightness pre-set, flash duration corresponds to pulse-length
  - connection: M5 plug at lighting controller
  - metal casing, optical material: PMMA
  - multiple mounting options
  - new improved version ("-a")
-

---

## Technical data

|                           |                                 |
|---------------------------|---------------------------------|
| Luminous field            | 7 mm x 75 mm                    |
| Light colour              | Red, 625 nm                     |
| Light design              | Diffus                          |
| Radiance                  | 192 W/(m <sup>2</sup> sr)       |
| Luminance                 | 24000 cd/m <sup>2</sup>         |
| Operation voltage         | 24 VDC (12 - 30 V)              |
| Ambient temperature       | -10°C bis +45°C                 |
| Degree of protection      | IP50                            |
| Housing material          | Aluminium black anodised        |
| Weight                    | 25 g                            |
| Risk group (DIN EN 62471) | Freie Gruppe                    |
| Safety class              | III, Schutzkleinspannung (SELV) |

---

---

**Accessories for Area and Bar lights - LDL7x75-R625/24V/EX/-a**

| Order number                           | Title                      | Description                                                                           |
|----------------------------------------|----------------------------|---------------------------------------------------------------------------------------|
| <b><i>Mounting Systems</i></b>         |                            |                                                                                       |
| 1-16-826                               | Tension clamp LxL7 series  | for variable attachment and extension of the LxL7 series, l=25mm, w=17mm              |
| <b><i>Connection cable M5-4pin</i></b> |                            |                                                                                       |
| 1-11-117                               | Cable-M5-4p-1A-straight-2m | 4x0.14mm <sup>2</sup> , 1A, 60V, PUR, IP67, M5-4pin straight socket to free cable end |
| 1-11-116                               | Cable-M5-4p-1A-straight-5m | 4x0.14mm <sup>2</sup> , 1A, 60V, PUR, IP67, M5-4pin straight socket to free cable end |
| 1-11-105                               | Cable-M5-4p-1A-angled-2m   | 4x0.14mm <sup>2</sup> , 1A, 60V, PUR, IP67, M5-4pin angled socket to free cable end   |
| 1-11-104                               | Cable-M5-4p-1A-angled-5m   | 4x0.14mm <sup>2</sup> , 1A, 60V, PUR, IP67, M5-4pin angled socket to free cable end   |

---

## Drawings



### light unit



### controller unit



Dimensional drawing in mm: length = 75 mm; width = 7 mm

| Function          | Symbol | Cable Colour* | Pin | Contact arrangement |
|-------------------|--------|---------------|-----|---------------------|
| Operating Voltage | V+     | brown         | 1   |                     |
| Ground            | GND    | blue          | 3   |                     |
| Switch Input      | ON/OFF | black         | 4   |                     |
| Not connected     | NC     | white         | 2   |                     |

\* for recommended accessories

Pin assignments, M5 connector