
vicotar® Telecentric Lens - T24/2.5a

Short description:	Telecentric Lens, C-mount, Sensor opt. 2/3", variable aperture, W/NIR
Order number:	2-05-234
EAN:	4251692620069



Characteristics

- telecentric measurement objective with object-sided telecentric beam path
 - high resolution, low-distortion, low telecentric error
 - available with image scale 1.5x, 2x, 2.5x and 3x
 - color-optimized and bright
 - adjustable aperture, arrestable
 - robust industrial design
 - direct attachment of the ring light RK1220 possible
-

Technical data

Image scale	2.47
Spectral range	380 nm - 900 nm
Working distance	31.7 mm
Camera distance (object-camera flange)	109.7 mm
Object field diagonal (max.)	4.4 mm
Sensor format (opt.)	2/3"
Image field diagonal (max.)	11 mm
Suitable for camera resolution	4.9 MPixel
Recommended pixel size	3.45 μ m
Aperture	variable (F11 - F64)
Lens mount	C-Mount
Filter thread, camera-side	M20.5 x 0.5
Weight	125 g
Usable object field with:	
• 2/3" sensor (8.8 x 6.6 mm ²)	3.6 mm x 2.7 mm
• 1/1.8" sensor (7.1 x 5.4 mm ²)	2.9 mm x 2.2 mm
• 1/2" sensor (6.4 x 4.8 mm ²)	2.6 mm x 1.9 mm
• 1/3" sensor (4.8 x 3.6 mm ²)	1.9 mm x 1.5 mm

Can be combined with

Order number	Title	Description
<i>RK1220-24V-BA series</i>		
1-10-243	RK1220-B470-24V/BA	ring light, blue, coaxial, If diameter: 24/40 mm, static/switchable
1-10-244	RK1220-W5K7-24V/BA	ring light, white, coaxial, If diameter: 24/40 mm, static/switchable
1-10-245	RK1220-IR850-24V/BA	ring light, IR850, coaxial, If diameter: 24/40 mm, static/switchable
1-10-241	RK1220-R633-24V/BA	ring light, red, coaxial, If diameter: 24/40 mm, static/switchable
1-10-242	RK1220-G525-24V/BA	ring light, green, coaxial, If diameter: 24/40 mm, static/switchable

Accessories for Telecentric Lenses - T24/2.5a

Order number	Title	Description
<i>Lens mount</i>		
2-90-122	Lens Holder d32	Holder for telecentric lenses and lightings with d = 32 mm
<i>Extension tubes</i>		
2-90-415	Extension ring 0.5 mm	26 x 31 x 0.5 reduces the minimum object distance (MOD)
2-90-416	Extension ring 1.0 mm	26 x 31 x 1.0 reduces the minimum object distance (MOD)
<i>Thread adapter c-mount</i>		
5-00-011	Thread adapter C-Mount-M42	Adapter for mounting of lenses with C-mount on cameras with M42x1 mount
2-90-414	CS to C-mount adapter 5.0 mm	for connecting C-mount lenses with CS-mount cameras, length: 5 mm
<i>Daylight blocking filter</i>		
2-91-131	IR filter M20.5x0.5	long-pass filter from 830 nm, daylight absorbing filter, filter thread M20.5x0.5
<i>Colour filter red</i>		

Order number	Title	Description
2-91-259	Colour filter red M20.5x0.5	long-pass filter from 630 nm, red, filter thread M20.5x0.5
