
vicotar® Telecentric Lens - TO42/16.4-232-V-LD

Short description: Telecentric Lens, C-Mount, Sensor max. 1",
aperture F6 - F22, long distan

Order number: 2-05-648



Characteristics

- telecentric measurement objective with object-sided telecentric beam path
 - long working distance
 - Designed for monochromatic applications
 - very well suited for blue LEDs including "Deep Blue" LEDs
 - high resolution, low-distortion, low telecentric error
 - adjustable aperture with identification of the aperture numbers, arrestable
 - robust industrial design
-

Technical data

Image scale	0.390
Spectral range	400 nm - 950 nm, (monochromatic)
Working distance	232 mm
Camera distance (object-camera flange)	420 mm
Object field diagonal (max)	42 mm
Sensor format (max)	1"
Image field diagonal (max)	16.4 mm
Suitable for camera resolution	10.3 MPixel
Recommended pixel size	3.45 µm
Aperture	variable (F8 - F22)
Lens mount	C-Mount
Filter thread, object-side	M52 x 0.75
Filter thread, camera-side	M20.5 x 0.5
Weight	325 g
Usable object field with:	
• 1" sensor (12.8 x 9.6 mm ²)	32.8 mm x 24.6 mm
• 2/3" sensor (8.8 x 6.6 mm ²)	22.6 mm x 16.9 mm
• 1/1.8" sensor (7.1 x 5.4 mm ²)	18.2 mm x 13.8 mm
• 1/2" sensor (6.4 x 4.8 mm ²)	16.4 mm x 12.3 mm

Can be combined with

Order number	Title	Description
<i>TZB51-UDC-a Serie</i>		
1-10-941	TZB51-B470/UDC/-a	telecentric light, blue, If diameter: 49 mm, flashable by flash controller
1-10-943	TZB51-IR880/UDC/-a	telecentric light, IR850, If diameter: 49 mm, flashable by flash controller
1-10-940	TZB51-R625/UDC/-a	telecentric light, red, If diameter: 49 mm, flashable by flash controller
1-10-944	TZB51-G525/UDC/-a	telecentric light, green, If diameter: 49 mm, flashable by flash controller
<i>TZB51 series</i>		
1-10-201	TZB51-B470-24V	telecentric light, blue, If diameter: 49 mm, static, cable open-ended
1-10-202	TZB51-IR880-24V	telecentric light, IR850, If diameter: 49 mm, static, cable open-ended
1-10-200	TZB51-R625-24V	telecentric light, red, If diameter: 49 mm, static, cable open-ended
1-10-215	TZB51-G525-24V	telecentric light, green, If diameter: 49 mm, static, cable open-ended
<i>R-CLR-69-SL series</i>		
1-33-007	R-CLR-69x41-B470-SL	ring light, blue, coaxial, If diameter: 41/69 mm, smart light technology
<i>RK2036-24V series</i>		
1-29-602	RK2036-B470-24V/C	ring light, blue, coaxial, If diameter: 41/69 mm, controlled, pot.: 0-10V,
<i>R-CLR-100-SL series</i>		
1-33-012	R-CLR-100x73-B470-SL	ring light, blue, coaxial, If diameter: 73/100 mm, smart light technology
<i>RK3652-24V series</i>		
1-29-702	RK3652-B470-24V/C	ring light, blue, coaxial, If diameter: 73/100 mm, controlled, pot.: 0-10V,
<i>R-CLR-132-SL series</i>		

Order number	Title	Description
1-33-017	R-CLR-132x104-B470-SL	ring light, blue, coaxial, If diameter: 104/132 mm, smart light technology
<i>RK5268-24V series</i>		
1-29-802	RK5268-B470-24V/C	ring light, blue, coaxial, If diameter: 104/132 mm, controlled, pot.: 0-10V,

Accessories for Telecentric Lenses - T042/16.4-232-V-LD

Order number	Title	Description
<i>Adjustment Aids</i>		
5-10-112	Adjustment aid 10	for easy adjustment to 10 mm depth of field, for image scale 0.5 - 0.2
<i>Lens mount</i>		
2-90-122	Lens Holder d32	Holder for telecentric lenses and lightings with d = 32 mm
<i>Extension tubes</i>		
2-90-415	Extension ring 0.5 mm	26 x 31 x 0.5 reduces the minimum object distance (MOD)
2-90-416	Extension ring 1.0 mm	26 x 31 x 1.0 reduces the minimum object distance (MOD)
2-90-419	Extension ring 0.1 mm	25.5 x 29 x 0.1 reduces the minimum object distance (MOD)
2-90-420	Extension ring 0.2 mm	25.5 x 29 x 0.2 reduces the minimum object distance (MOD)
<i>Lens adapter c-mount</i>		
2-90-414	CS to C-mount adapter 5.0 mm	for connecting C-mount lenses with CS-mount cameras, length: 5 mm
<i>Neutral density filter</i>		
2-91-174	ND filter 3.0 M52x0.75	optical density 3.0 - 0.1% transmission, f-stop reduction 10, filter thread M52x0.75
2-91-164	ND filter 1.2 M52x0.75	optical density 1.2 - 6.3% transmission, f-stop reduction 4, filter thread M52x0.75

Order number	Title	Description
2-91-154	ND filter 0.6 M52x0.75	optical density 0.6 - 25% transmission, f-stop reduction 2, filter thread M52x0.75
Daylight blocking filter		
2-91-131	IR filter M20.5x0.5	long-pass filter from 830 nm, daylight absorbing filter, filter thread M20.5x0.5
2-91-134	IR filter M52x0.75	long-pass filter from 830 nm, daylight absorbing filter, filter thread M52x0.75
Polarising filters		
2-91-144	Pole filter M52x0.75	linear polarizing filter, range 420 nm - 780 nm, filter thread M52x0.75
Colour filter blue		
2-91-290	Colour filter blue M52x0.75	band-pass filter, range 350 nm - 600 nm, filter thread M52x0.75
UV Cut-Off Filter		
2-91-124	UV blocking filter M52x0.75	long-pass filter from 350 nm, usable as protective glass, filter thread M52x0.75
Colour filter red		
2-91-259	Colour filter red M20.5x0.5	long-pass filter from 630 nm, red, filter thread M20.5x0.5
2-91-262	Colour filter red M52x0.75	long-pass filter from 630 nm, red, filter thread M52x0.75
Colour filter green		
2-91-303	Colour filter green M52x0.75	band-pass filter, range 430 nm - 620 nm, filter thread M52x0.75
Colour filter yellow		
2-91-277	Colour filter yellow M52x0.75	long-pass filter from 530 nm, yellow, filter thread M52x0.75
Deflection mirror 90° series		
2-25-115	Deflection mirror 90-56	90° deflection, attachment for telecentric lenses and lightings with d = 56 mm
Adapters for attaching lights to lenses		

Order number	Title	Description
1-29-676	Adapter ring d41 - M52x0.75	for R-CLR-69x41 and RK2036, for attachment to lenses with filter thread M52x0.75
1-29-772	Adapter ring d73 - M52x0.75	for R-CLR-100x73 und RK3652, for attachment to lenses with filter thread M52x0.75
Beam splitter STE60x60		
1-20-050	STE60x60-VIS	Beam splitter unit for coaxial light system, optimized for 450-700 nm
1-20-022	Adapter STE60x60 - TZ056	Attachment of the STE60x60 to telecentric lenses and lightings with d = 56mm

Drawings



Dimensional drawing in mm