
Camera for vicosys® - Manta G-2460C PoE

Short description: GigE-Camera, color, C-Mount, 24.6 MP, 5,328 x 4,608 Pixel, 1.2"

Order number: 3-12-691



Characteristics

- GigE area scan camera for industrial applications
 - 1.2" sensor with resolution of 5,328 x 4,608 (color)
 - industrial GigE Vision interface with Power over Ethernet
 - standard housing with class IP30
 - compatible with C-Mount lenses
-

Technical data

Sensor Specification

Sensor name	Sony IMX540
Spectrum	VIS (color)
Shutter technology	Global Shutter
Sensor format	1,2"
Sensor diagonal [mm]	19.30
Total resolution [Pixel]	5,328 x 4,608
Total pixel [MP]	24.6
Pixel size [µm]	2.74
Sensor technology	Pregius S
Sensor alternatives (same technology)	IMX530 (more FPS)

Camera Specification

Family	Allied Vision Manta
Type	Areascan Camera
IR blocking filter	Yes
LAN speed [MBit/s]	1000
Protection class	IP30
Frame rate [fps]	4.9

General Information


POE	yes
Lens Mount	C-Mount
Weight [g]	190
Housing dimensions	86 mm x 44 mm x 29 mm

Accessories for Cameras for Multi-Camera Systems - Manta G-2460C PoE

Order number	Title	Description
<i>Ethernet Cables for Cameras</i>		
4-40-320	Ethernet-Allied-D-1m	Ethernet Cable for Allied Cameras, drag chain suitable, 1m
4-40-325	Ethernet-Allied-D-30m	Ethernet Cable for Allied Cameras, drag chain suitable, 30m
4-40-324	Ethernet-Allied-D-20m	Ethernet Cable for Allied Cameras, drag chain suitable, 20m
4-40-323	Ethernet-Allied-D-10m	Ethernet Cable for Allied Cameras, drag chain suitable, 10m
4-40-322	Ethernet-Allied-D-5m	Ethernet Cable for Allied Cameras, drag chain suitable, 5m
4-40-321	Ethernet-Allied-D-3m	Ethernet Cable for Allied Cameras, drag chain suitable, 3m
4-40-319	Ethernet-Allied-10m	Ethernet Cable for Allied Cameras, 10m
4-40-318	Ethernet-Allied-5m	Ethernet Cable for Allied Cameras, 5m
4-40-317	Ethernet-Allied-3m	Ethernet Cable for Allied Cameras, 3m
<i>POE Injector</i>		
4-40-341	POE-TI-IG30	POE injector for all Gigabit Ethernet Cameras
4-40-339	POE-LACPI30	POE injector for Allied GigE Cameras
4-40-338	POE-TL-POE150S	POE injector for Allied GigE Cameras
<i>Power Supply</i>		
4-40-334	Netzteil-HR10-10P-12S	Power Supply for Prosilica and Manta Cameras
<i>Trigger Cables</i>		
4-40-303	SPS-Power-Kabel-HR10-AVT-2m	I/O Cable for Prosilica, Goldeye and Manta Cameras, 2m
4-40-311	SPS-Power-Kabel-HR10-AVT-10m	I/O Cable for Prosilica, Goldeye and Manta Cameras, 10m
4-40-310	SPS-Power-Kabel-HR10-AVT-5m	I/O Cable for Prosilica, Goldeye and Manta Cameras, 5m

Order number	Title	Description
4-40-306	Buchse-HR10LP-10S-12S	Connector Hirose angled for Prosilica, Goldeye and Manta Cameras
4-40-305	Buchse-HR10P-10S-12S	Connector Hirose straight for Prosilica, Goldeye and Manta Cameras
4-40-304	SPS-Power-Kabel-HR10-AVT-3m	I/O Cable for Prosilica, Goldeye and Manta Cameras, 3m
Mounting Plates		
4-40-313	Tripod-Mount-Manta	Manta Mounting Plate, M6 threads and 1/4" UNC

Drawings



Dimensional drawing in mm